according to 1907/2006/EC



Revision: April 1, 2024

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

# 1.1 Product identifier beginning with lot number 20041 A64

· Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

· Other means of identification: No other identifiers

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

• Application of the substance / the mixture: Lubricant

· Uses advised against: No further relevant information available.

 1.3 Details of the supplier of the Safety Data Sheet
 Manufacturer/Supplier: Kano Laboratories LLC
 24 DaVinci Dr., P.O. Box 405
 Bohemia, NY 11716
 Telephone: 631-567-5300
 Email: info@super-lube.com

# 1.4 Emergency telephone number:

ChemTel

1-800-255-3924 (US/Canada), 1-813-248-0585 (International), 1-300-954-583 (Australia), 0-800-591-6042 (Brazil), 400-120-0751 (China), 000-800-100-4086 (India), 800-099-0731 (Mexico)

# **SECTION 2: Hazards identification**

#### • 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

Aerosol 2 H223-H229 Flammable aerosol. Pressurised container: May burst if heated.

- Skin Irrit. 2 H315 Causes skin irritation.
- STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

# <sup>•</sup> 2.2 Label elements

# · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light

· Hazard statements

H223-H229 Flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

(Cont'd. on page 2)

according to 1907/2006/EC

#### Revision: April 1, 2024

#### Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

(Cont'd. from page 1) P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 Do not pierce or burn, even after use. P261 Avoid breathing mist/vapours/spray. Wear protective gloves. P280 P302+P352 IF ON SKIN: Wash with plenty of soap and water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. • 2.3 Other hazards There are no other hazards not otherwise classified that have been identified. Results of PBT and vPvB assessment · **PBT:** Not applicable.

· vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

#### <sup>•</sup> 3.2 Mixtures

· Components:

components.					
Ī	CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	50-75%		
	EINECS: 265-149-8	🚯 Asp. Tox. 1, H304			
	Index number: 649-422-00-2	Aquatic Chronic 2, H411			
		🚯 Skin Irrit. 2, H315; STOT SE 3, H336			
Ē	CAS: 74-98-6	Propane	10-20%		
	EINECS: 200-827-9	🚸 Flam. Gas 1, H220			
	Index number: 601-003-00-5	Press. Gas (Comp.), H280			
	Reg.nr.: 01-2119486944-21-XXXX				
	Additional information: For the wording of the listed Hazard Statements refer to section 16.				

#### **SECTION 4: First aid measures**

#### <sup>•</sup> 4.1 Description of first aid measures

#### · After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

#### • After skin contact:

Immediately remove any clothing soiled by the product. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

#### • After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while lying on their back should be turned onto their side.

(Cont'd. on page 3)

according to 1907/2006/EC

Revision: April 1, 2024

Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

• 4.2 Most important symptoms and effects, both acute and delayed

(Cont'd. from page 2)

Irritant to skin and mucous membranes. Frostbite Coughing Dizziness Breathing difficulty Nausea **4.3 Indication of any immediate med** 

## • 4.3 Indication of any immediate medical attention and special treatment needed

Treat frost-bitten areas appropriately.

## **SECTION 5: Firefighting measures**

• **5.1 Extinguishing media** • **Suitable extinguishing agents:** Foam Carbon dioxide Fire-extinguishing powder Gaseous extinguishing agents Water haze or fog

• For safety reasons unsuitable extinguishing agents: Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Danger of receptacles bursting because of high vapour pressure when heated.

#### <sup>•</sup> 5.3 Advice for firefighters

#### Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

#### • Additional information:

In case of leakage, eliminate all ignition sources.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Cool endangered receptacles with water fog or haze.

# **SECTION 6: Accidental release measures**

# · 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Use personal protective equipment as required.

Particular danger of slipping on leaked/spilled product.

Keep away from ignition sources.

Protect from heat.

#### <sup>•</sup> 6.2 Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

# 6.3 Methods and material for containment and cleaning up

#### Towel or mop up material and collect in a suitable container.

For large spills, absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Do not flush with water or aqueous cleansing agents

(Cont'd. on page 4)

according to 1907/2006/EC

Revision: April 1, 2024

#### Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

(Cont'd. from page 3)

Send for recovery or disposal in suitable receptacles.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Keep out of reach of children.

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Avoid splashes or spray in enclosed areas.

#### · Information about fire - and explosion protection:

Protect against electrostatic charges.

Emergency cooling must be available in case of nearby fire.

Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

#### 7.2 Conditions for safe storage, including any incompatibilities

• Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Avoid storage near extreme heat, ignition sources or open flame.

• Information about storage in one common storage facility: Store away from oxidising agents. • Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

## 74-98-6 Propane

OEL (Ireland) Asphx

· DNELs: No further relevant information available.

· PNECs: No further relevant information available.

#### <sup>•</sup> 8.2 Exposure controls

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

#### **Respiratory protection:**

Not required under normal conditions of use.

(Cont'd. on page 5)

# Safety data sheet according to 1907/2006/EC

Revision: April 1, 2024

# Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

	(Cont'd. from page 4) Use suitable respiratory protective device in case of insufficient ventilation. For spills, respiratory protection may be advisable. <b>Protection of hands:</b>					
Protective gloves						
The glove material has to be impermeab	The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. <b>Eye protection:</b>					
Safety glasses	Safety glasses					
<ul> <li>Body protection: Protective work clothing</li> <li>Limitation and supervision of exposure into the environment: Avoid release to the environment.</li> <li>Risk management measures: No further relevant information available.</li> </ul>						
SECTION 9: Physical and chem	ical properties					
• 9.1 Information on basic physical and chemical properties						
Form:	Aerosol					
Colour:	Translucent					
· Odour:	Hydrocarbon.					
· Odour threshold:	Not determined.					
· pH-value:	Not determined.					
Melting point/freezing point:	Not applicable, as aerosol.					
Initial boiling point and boiling range:	Not applicable, as aerosol.					
· Flash point:	Not applicable, as aerosol.					

pri-value.	Not determined.
<ul> <li>Melting point/freezing point:</li> </ul>	Not applicable, as aerosol.
<ul> <li>Initial boiling point and boiling ran</li> </ul>	<b>ige:</b> Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gas):	Flammable aerosol.
· Auto/Self-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Explosive properties:	Not determined.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidising properties	Non-oxidising.
· Vapour pressure:	Not determined.
· Density:	
Relative density:	<1
Vapour density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
	(Cont'd. on pa

according to 1907/2006/EC

Revision: April 1, 2024

# Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

water: Partition coefficient: n-octanol/wate /iscosity Dynamic: Kinematic at 40 °C: 0.2 Other information	Not determined. 240-260 cSt <b>Maximum Incremental Reactivity (MIR) value:</b> 0,39		
/iscosity Dynamic: Kinematic at 40 °C:	Not determined. 240-260 cSt <b>Maximum Incremental Reactivity (MIR) value:</b> 0,39		
Dynamic: Kinematic at 40 °C:	240-260 cSt Maximum Incremental Reactivity (MIR) value: 0,39		
Kinematic at 40 °C:	240-260 cSt Maximum Incremental Reactivity (MIR) value: 0,39		
	Maximum Incremental Reactivity (MIR) value: 0,39		
0.2 Other information			
	Flame Projection: 23 inches (58.4 cm) Flash Back: 3 - 4 inches (7.6 – 10.2 cm)		
<ul> <li>Thermal decomposition / conditions to be avoided:</li> <li>Danger of receptacles bursting because of high vapour pressure when heated.</li> <li>10.3 Possibility of hazardous reactions</li> </ul>			
	cuons		
lammable aerosol.			
Tammable aerosol. Develops readily flammable gases/fum	ies.		
Tammable aerosol. Develops readily flammable gases/fum Can form explosive mixtures in air if he Jsed empty containers may contain pr			
Tammable aerosol. Develops readily flammable gases/fum Can form explosive mixtures in air if he Jsed empty containers may contain pr Reacts with oxidising agents.	ies. eated above flash point and/or when sprayed or atomised. oduct gases which form explosive mixtures with air.		
Tammable aerosol. Develops readily flammable gases/fum Can form explosive mixtures in air if he Jsed empty containers may contain pr Reacts with oxidising agents. Toxic fumes may be released if heated	ies. eated above flash point and/or when sprayed or atomised. oduct gases which form explosive mixtures with air.		
Elammable aerosol. Develops readily flammable gases/fum Can form explosive mixtures in air if he Jsed empty containers may contain pr Reacts with oxidising agents. Toxic fumes may be released if heated <b>0.4 Conditions to avoid</b>	ies. eated above flash point and/or when sprayed or atomised. oduct gases which form explosive mixtures with air. I above the decomposition point.		
Tammable aerosol. Develops readily flammable gases/fum Can form explosive mixtures in air if he Jsed empty containers may contain pr Reacts with oxidising agents. Toxic fumes may be released if heated	nes. eated above flash point and/or when sprayed or atomised. oduct gases which form explosive mixtures with air. I above the decomposition point. moke.		

Carbon monoxide and carbon dioxide

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

· Acute toxicity: Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

#### 64742-47-8 Distillates (petroleum), hydrotreated light

Oral LD50 >5000 mg/kg (rat) Dermal LD50 >2000 mg/kg (rabbit)

#### Primary irritant effect

· Skin corrosion/irritation:

Causes skin irritation.

· Serious eye damage/irritation: Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

(Cont'd. on page 7)

according to 1907/2006/EC

Revision: April 1, 2024

#### Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

(Cont'd. from page 6)

#### · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

#### · Probable routes of exposure:

Inhalation.

Eye contact.

Skin contact.

· Germ cell mutagenicity: Based on available data, the classification criteria are not met.

· Carcinogenicity: Based on available data, the classification criteria are not met.

• Reproductive toxicity: Based on available data, the classification criteria are not met.

- STOT-single exposure:
- May cause drowsiness or dizziness.

• STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

# **SECTION 12: Ecological information**

<sup>·</sup> 12.1 Toxicity

• Aquatic toxicity: Toxic to aquatic life with long lasting effects.

- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · Additional ecological information:

· General notes: Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

# **SECTION 13: Disposal considerations**

#### <sup>·</sup> 13.1 Waste treatment methods

#### · Recommendation

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

· 14.1 UN-Number

· DOT, ADR/RID/ADN, IMDG, IATA

UN1950

# <sup>•</sup> 14.2 UN proper shipping name

(Cont'd. on page 8)


# Safety data sheet according to 1907/2006/EC

Revision: April 1, 2024

	(Cont'd. from p
DOT ADR/RID/ADN, IMDG IATA	Aerosols AEROSOLS Aerosols, flammable
14.3 Transport hazard class(es)	
DOT	
Class	2.1
Label	2.1
ADR/RID/ADN	
Class	2.1 5F
Label IMDG, IATA	2.1
Class	2.1
Label	2.1
14.4 Packing group	Aerosols are not assigned a packing group.
14.5 Environmental hazards:	Product contains environmentally hazard substances: Distillates (petroleum), hydrotres light
Marine pollutant:	5
Yes	
14.6 Special precautions for user	Not applicable.
Hazard identification number (Kemler code): EMS Number:	- F-D,S-U
4.7 Transport in bulk according to Annex II f Marpol and the IBC Code Not applicable.	
Transport/Additional information:	
DOT	

according to 1907/2006/EC

Revision: April 1, 2024



# **SECTION 15: Regulatory information**

<sup>•</sup> 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· Other regulations, limitations and prohibitive regulations

• Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

(Cont'd. on page 10)

# Trade name: Super Lube® Multi-Purpose Synthetic Lubricant with Syncolon® (aerosol)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal dose, 50 percent DBT: Persistant, Bio-accumulable, Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 2: Aerosols – Category 2 Press. Gas (Comp.): Gases under pressure – Compressed gas Skin Irrit. 2: Skin corrosion/Irritation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 <b>Sources</b> Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/regist overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Verron, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Cu	
	ırtis D., ed., ISBN:
SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com	