

TECHNICAL DATA SHEET

SUPER LUBE® SUPER KLEEN CLEANER/DEGREASER

March 2024

PRODUCT DESCRIPTION:

Super Lube® Super Kleen Cleaner/Degreaser is a specially formulated, industrial strength, multi-purpose non-solvent solution designed for cleaning dirt, grease, grime and ink on virtually any water safe surface. Super Lube® Super Kleen Cleaner/Degreaser works effortlessly. Use full strength or dilute as required.



FEATURES:

- ❖ pH = 9 (concentrate)
- ❖ Contains no solvents
- ❖ Non-flammable
- ❖ NSF Registered A1, #151517, General cleaner

TYPICAL APPLICATIONS:

- ❖ Basin style parts washer
- ❖ Compressors
- ❖ Glass surfaces
- ❖ Concrete
- ❖ Counter tops
- ❖ Engines
- ❖ Floors
- ❖ Forklifts
- ❖ Grease traps
- ❖ Hard surfaces
- ❖ Machinery
- ❖ Tools
- ❖ Food processing equipment

PACKAGE SIZES:

Part No.	Description
10004	4 oz. Mist Spray Bottle
10032	1 Quart Trigger Sprayer Bottle
10001	1 Gallon Bottle
10005	5 Gallon Pail
10060	55 Gallon Drum

PROPERTIES:

Test	Rating
Color:	Clear
Scent:	Mild
pH:	9 (concentrate)
Viscosity:	Water thin
Solubility in water:	Soluble
Specific gravity:	1.03
Appearance:	Liquid
Flash Point °F (°C):	None

E. COLI TEST:



TECHNICAL DATA SHEET

SUPER LUBE® SUPER KLEEN CLEANER/DEGREASER

March 2024

The following are the results of a test for E. coli:

McFarland 0.5 Suspension: Initial assay: 1.5×10^8 CFU/ml

Time of Incubation	CFU/ml	Log Inhibition	Percent Inhibition
Initial Sample	0	>5.18	100
1 Day	0	>5.18	100

McFarland 0.5 Suspension: After 24 hours of incubation 1.3×10^8 CFU/ml

[Scan the QR code below or click here for more information on this test.](#)



SALMONELLA TEST:

McFarland 0.5 Suspension: Initial assay: 1.5×10^8 CFU/ml

Time of Incubation	CFU/ml	Log Inhibition	Percent Inhibition
Initial Sample	0	>5.18	100
1 Day	0	>5.18	100

McFarland 0.5 Suspension: After 24 hours of incubation 1.3×10^8 CFU/ml

[Scan the QR code below or click here for more information on this test.](#)



DIRECTIONS:



TECHNICAL DATA SHEET

SUPER LUBE® SUPER KLEEN CLEANER/DEGREASER

March 2024

For use on:	Dilution:	To apply:
Concrete floors, floors (to remove wax), greasy engines, white wall tires.	Use full-strength or 1 part cleaner and 2 parts water	Scrape heavy deposits. Spray or brush on. Let stand. Brush encrusted areas. Hose or wipe off.
Aircraft equipment, batteries, garage walls, machinery, marine equipment, ovens, fan ducts, plastic seals, rubber mats, rugs, carpets, upholstery, work benches.	Use 1 part cleaner and 3 parts water.	Spray or apply with dampened cloth. Agitate with brush if necessary. Hose or wipe off.
Aluminum, formica, stainless steel, walls, woodwork (clean from the bottom up), tools, venetian blinds, general cleaning.	Use 1 part cleaner and 6 parts water.	Spray or mop on. Wipe or mop off. If surface has long-lasting grime, use hot water.
Porcelainware, terrazzo, tile.	Use 1 part cleaner and 10 parts water.	Spray or apply with dampened cloth or sponge. Wipe off.

SHELF LIFE / WARRANTY:

Super Lube® products have a five (5) year recommended shelf life when stored in the original container and in reasonable ambient conditions. The warranty period is twenty-four (24) months from the date of purchase. For complete information visit www.super-lube.com/what-is-the-shelf-life-ezp-320.html.



See Safety Data Sheet (SDS) for further details regarding safe use of this product.



Made in USA

The information provided in this Technical Data Sheet including the recommendations for use and application of the product are based on our knowledge and experience of the product as of the date of this bulletin. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Kano Laboratories LLC is, therefore not liable for the suitability of our product for the production processes and conditions in respect for which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

All Super Lube® trademarks in this document are trademarks of Kano Laboratories LLC.